MATERIAL SAFETY DATA SHEET

16

SECTION I - IDENTIFICATION

Company Name:

St. Marys Carbon Company

Address:

1939 State Street

St. Marys, PA 15857

Product Name:

CARBON/GRAPHITE PRODUCTS

Chemical Name:

MIXTURE

Date Prepared:

01/02/03

Replaces:

01/21/02

Least

Slight 1 **Hazard Rating**

Moderate

High

Extreme

3

Reactivity = 0

Telephone: (814) 781-7333

Prepared by: Phil Schlosser

#2 / \$1 min

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT

PERCENT

C.A.S. NO.

CARBON/GRAPHITE, NATURAL

>90%

7740-44-0/7782-42-5

1

*SILICA, CRYSTALLINE QUARTZ

Not Determined

14808-60-7

SECTION III - OCCUPATIONAL EXPOSURE LIMITS

OSHA PEL:

Graphite -2.5 mg/cubic meter (respirable)

Silica - 0.1 mg/cubic meter (respirable)

ACGIH TLV:

Graphite -2 mg/cubic meter (respirable)

Silica - 0.1 mg/cubic meter (respirable)

CARCINOGEN:

NTP - no

IARC - *yes OSHA - no

St. Marys Carbon Company

SECTION IV - HEALTH HAZARDS

Effects of exposure: Prolonged and repeated overexposure to dust may lead to pneumoconiosis.

Dust particles may cause mechanical irritation to the eyes and skin. Individuals with pre-existing chronic respiratory impairment may be at

increased risk of pneumoconiosis.

SECTION V - EMPLOYEE PROTECTION

Respiratory Protection: NIOSH approved respirator for dust if exposures are expected to

exceed the PELs.

Eye Protection: Safety glasses with side shields if there is a danger of flying

particles.

Protective Gloves: Recommended.

Other Protective No.

Equipment:

Normal work clothing.

Ventilation: At point of operation if machining or other dust-creating activities

are performed.

SECTION VI - FIRST AID

Skin Contact: Wash affected area with soap and water especially before eating, smoking,

and at the end of work shift.

Eye Contact: Do not rub eyes; immediately flush eyes with plenty of water for at least

15 minutes. Call a physician if irritation persists.

Inhalation: Remove to fresh air and administer artificial respiration if breathing has

stopped; oxygen may also be administered. Seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention.

MATERIAL SAFETY DATA SHEET

16

SECTION VII - FIRE EXPLOSION DATA

Flash Point (method used):

Does not flash

Flammable Limits:

N/A

LEL:

UEL:

Extinguishing Media:

Water fog, carbon dioxide, foam.

Special Fire Fighting

Procedures:

Use self-contained breathing apparatus.

Unusual Fire and Explosion

Hazards:

Carbon/Graphite dust is normally not explosive, but it may weakly contribute if the event is initiated by another explo-

sive dust or gas.

SECTION VIII - SPECIAL PRECAUTIONS

Precautions for Handling and Storing:

Handle in a manner which minimizes airborne dust.

Other Precautions: Graphite dust is electrically conductive; dust accumulations may cause

electrical short circuits or other malfunctions.

SECTION IX - ENVIRONMENTAL PROTECTION

Spill or Leak Procedures:

Normal housekeeping practices; sweep, shovel, or vacuum clean-

up with a HEPA filter,

Waste Disposal Method:

Dispose of according to local, state, and federal regulations.

SECTION X - PHYSICAL DATA

Boiling Point (F)

N/A

Vapor Pressure (mm Hg)

N/A

Specific Gravity (H2O=1)

1.2 - 2.0

MATERIAL SAFETY DATA SHEET

16

Vapor Density (Air=1)

N/A

Evaporation Rate (Butyl Alcohol=1)

N/A

Solubility in Water

Insoluble

Percent Volatile by Volume

N/A

Appearance / Odor

Dark gray to black / no odor

SECTION XI - REACTIVITY DATA

Unstable Stable

Hazardous

Polymerization: [| May Occur [•] Will not

occur

Conditions and Materials to Avoid:

Strong oxidizers.

Hazardous Decomposition Products:

Combustion produces carbon monoxide and carbon

dioxide.

SECTION XII - REFERENCES

ACGIH:

Documentation of Threshold Limit Values

OSHA:

29 CFR 1910.1000, Table Z-1

THIS PRODUCT SAFETY SHEET IS OFFERED SOLELY FOR YOUR INFOR-MATION, CONSIDERATION AND INVESTIGATION. THE INFORMATION AND DATA ARE TAKEN FROM SOURCES BELIEVED TO BE RELIABLE AND CORRECT, BUT CANNOT BE WARRANTED BY THE MANUFACTURER.

This is the end of MSDS 16.